

CONCIERGE™ Door Opener

Model 2300 Checklist

Please complete the following information before quoting or ordering equipment.





Customer Name		Today's Date	
Site Address	City	State	Zip
Phone	Cell Phone	Email	

Unit Type



Door Mount (pulls door open)

Unit mounted to door and arm attached to door frame



Jamb Mount (pushes door open)

Unit mounted to frame and arm attached to door



- Door Right (CONCIERGE 23DR) Door Left (CONCIERGE 23DL) Jamb Right (CONCIERGE 23JR) Jamb Left (CONCIERGE 23JL)

Getting Started

Door Location _____

Door Material* Wood (hollow) Wood (solid) Steel Aluminum/glass

Door Frame Material Wood Steel Aluminum/glass

Is there a door closer? (NOTE: If yes, the door closer must be removed.) Yes No

Door Height _____" Door Width _____"

* Door mount unit on light, hollow door will require thru boths (supplied).

Door Mount

Door swing In Out

What is the distance from wall to back of door when it's open to 90-degrees? (NOTE: Door mount unit requires at least 3½".) _____"

Is there at least 2½" of clearance above the top of door? (NOTE: This is required for arm assembly clearance) Yes No

Is there a suitable surface to mount the arm show to the door frame? Yes No

Jamb Mount

Avoid exterior "out" swinging door because there is no brake to hold the door open.

Reveal distance from back surface of unit to face of door? Standard jamb mount unit is 4½"; extended jamb mount unit is 7" _____".

Is there at least 6" of clearance above the top of door? Yes No

Is there a suitable surface to mount the arm show to the door frame? Yes No

Interior Door Application

- Are the hinges conventional butt hinges (without spring close)? Yes No
- Is an electric door strike required? Yes No
- If there is an existing strike, what is the voltage? _____" AC DC
- If strike is required, is it for a: Spring latch Dead bolt
- If there is a pair of doors, is there a mullion between them? Yes No
- Is there a 115 VAC receptacle within 9-feet? Yes No
- Type of Control Unit (wireless): Digital keypad Remote Wall control, plate (4 1/2" square) Pendant
- Is battery back-up recommended? Yes No Do you want it included? Yes No

Ordering Equipment

Follow these easy steps to select your perfect setup

STEP 1: Choose the main unit

- Jamb Right (CONCIERGE 23JR)
- Jamb Left (CONCIERGE 23JL)
- Door Right (CONCIERGE 23DR)
- Door Left (CONCIERGE 23DL)

STEP 2: Select at least one control unit (REQUIRED)

- Exterior Keypad (CONCIERGE KEM) **OR**
- Interior Push-pad (CONCIERGE PIM) **OR**
- 1-Button Remote (CONCIERGE RGD1) **OR**
- 1-Button Pendant (CONCIERGE RP1)

STEP 3: Select optional equipment

- 2-Button Remote (CONCIERGE RGD2)
- 4-Button Remote (CONCIERGE RGD4)
- Electric Strike Plate (CONCIERGE ESP)

Diagram

Please sketch any unusual construction or dimensions

